



IMPACT® 1040T

ELECTRIC AIRLESS SPRAYER

BUILT FOR SMOOTH TEXTURE & AGGRESSIVE COATINGS

The Impact 1040T is perfect for contractors that need a durable and dependable sprayer for level 5 finishes; knockdown texture and high build coatings.

Submerged Fluid Section

- The submerged foot valve creates the most efficient siphoning system on the market today, which handles heavy bodied coatings with ease
- Built with ceramic balls and carbide seats that are resistant to aggressive coatings
- PermaLife™ Cylinder never wears and never needs replacing
- Quad+ Packings are self-adjusting and self-compensating, extending life and delivering the best performance on every job

Smart Design

- EZ Tilt™ Cart allows for quick and easy change out and cleaning
 - ▀ Easily tilt back with one hand
- Field serviceable with a fast removal fluid section that can be changed out in minutes
- Electronic pressure control provides consistent pressure and eliminates the issues with deadband

WearGuard Warranty

- Best and longest warranty in the industry
 - ▀ Four-year manufacturer warranty
- Lifetime DuraLife™ Brushless HE Motor warranty



For more information contact your
Local Sales Representative.

Titan Tool

1770 Fernbrook Lane
Minneapolis, MN 55447
1-800-526-5362

INCLUDES RX-APEX™

Unfiltered gun with TR! 517 Tip

- ▶ 3/8" x 50' Hose
- ▶ 1/4" x 6' Whip Hose

AUTOOILER™

DURALIFE™ BRUSHLESS HE MOTOR

Optimized for every tip size and every applicator's technique.

PERMALIFE™ CYLINDER

Will never wear out.

QUAD+ PACKINGS

FAST-REMOVAL FLUID SECTION

T-slot piston and coarse thread make removal fast.

LARGE HOSE WRAP

Holds up to 150-feet of airless hose.

TELESCOPING HANDLE

ELECTRONIC PRESSURE CONTROL

Consistent pressure.
Zero deadband.

EZ-TILT CART

For easy clean up and pail changes.

LARGE 12" PNEUMATIC TIRES

Accessories

DESCRIPTION	PART NO.
Splatter Nozzle	765-360
M-4 Mastic Gun	289013
Filter Body	800-705
60-Mesh Filter	730-067
10-Mesh Filter	730-067-10
30-Mesh Filter	730-067-30
50' x 3/8" Air Hose	550891

DESCRIPTION	PART NO.
LS-10 Liquid Shield Plus 4 oz. Bottle	314-483
LS-10 Liquid Shield Plus 1 Qt. Bottle	521418
LS-10 Liquid Shield Plus 1 gal. Bottle	314-207
Piston Lube 4 oz. Bottle	314-481
Piston Lube 8 oz. Bottle	314-480
Piston Lube 1 Qt. Bottle	700-926

Specifications

SPECIFICATIONS	
Max. Delivery	1.15 GPM (4.36 LPM)
Max. Operating Pressure	3300 PSI (22.75 MPa)
Max. Tip Size (1 Gun)	0.033"
(2 Guns)	0.022"
Motor	2.50 HP Dura Life Brushless 120V
CONFIGURATIONS	
CONFIGURATIONS	PART NO.
High Rider	2405360

SPLATTER NOZZLE

For smooth texture applications including orange peel and knock down.

Air requirement 4-12 CFM at full open.



WearGuard Warranty

- ▶ Four-year manufacturer warranty
- ▶ Lifetime DuraLife™ brushless motor warranty



titantool.com

Titan Tool

1770 Fernbrook Lane
Minneapolis, MN 55447
1-800-526-5362