



PDG INDUSTRIAL ALTERNATORS
MAXIMUM ENGINEERING. MAXIMUM POWER.



PDG Industrial 184J - 40 kW
3 Phase PF .8 – 44 kW / 1 Phase PF .8 – 28 kW
1 Phase PF 1.0 – 40 kW

1800 rpm single bearing
Self exciting - Brushless, Synchronous.
1 phase 60 Hz 120/240
3 Phase 60 Hz 120/208, 120/240, or 277/480

100% PURE AMERICAN ESSEX® COPPER

2/3 Pitch Copper Windings are double dipped for extreme environment durability, providing the smooth, clean power needed for sensitive electronics as well as the raw power required for heavy motor applications.

PDG Industrial alternators are designed and built to withstand extreme conditions. They conform to IEC 34-1/34-2, BS 4999/5000 and IS: 4722-2001. The enclosure rating is IP 23 with Class H insulation, satisfying IEC 34-5/IS: 4691/DIN VDE 0530-5 requirements. They are dynamically balanced, brushless, and screen protected. They are self-excited and self-regulated through an AS440 AVR.

Our alternators have the following features:

1. +/- 1.0 % Voltage regulation (max.) in static conditions
2. IP: 23 protections with Insulation class H
3. Permissible overload of 10% for one hour in 12 hours of operation.
4. Excitation Boost System (EBS) for unparalleled motor starting capability.

3-PHASE CLASS H TEMPERATURE-RISE (125°C)										1-PHASE CLASS H TEMPERATURE-RISE (125°C)						
VOLTAGE		50HZ 1500RPM				60HZ 1800RPM				50HZ 1500RPM			60HZ 1800RPM			
STAR-SERIES		380	400	415	440	416	440	460	480	600	220	230	240	220	230	240
STAR-PARALLEL		190	200	208	220	208	220	230	240	300	110	115	120	110	115	120
Δ-SERIES		220	230	240	254	240	254	266	277	346						
184J	Rated Capacity(KVA)	40	42.5	40	40	47.3	50	50	50	55	28	28	28	35	35	35
	Rated Power(KW)	32	34	32	32	37.8	40	40	44	44	22.4	22.4	22.4	28	28	28
	Efficiency(%)	87.6	86.6	87.1	87.5	85.9	85.8	86.1	86.4	86.4	83	83	83	82.9	83	83
	Input power(KW)	37	39.3	36.7	36.6	44	46.7	46.5	46.3	46.3	27	27	27	33.8	33.8	33.8

*Chart is based on PF 1.0

Our generators have been designed for use in a maximum ambient temperature of 104°F/40°C and altitude less than 3280'/1000M above sea level.

Engine requirements: 60 HP Diesel / 80 HP Gasoline

PDG Industrial Alternator Warranty

Prime - 36 Months Prorated / Unlimited Hours

Standby – 60 Months Prorated / 2500 Hours (500 Hours max per year)

Complete warranty available upon request



Ask your local PDG Authorized Dealer about availability!

