

145 Newborn Road • Rutledge, GA 30663 706.557.1400 • <u>www.PROFOAM.com</u>

Section 1: Identification

Product Identifier

Trade Name:	B-PF-OC-500 PLUS
Chemical Name:	Polyurethane Resin
Recommended Use:	Component for the manufacture of Polyurethanes
Restrictions on Use :	

Chemical Manufacturer Information

Name:	PROFOAM	Phone:	(706) 557-1400
Address:	145 Newborn Road, Rutledge, GA	Fax:	(706) 557-1405
Website:	30663 www.PROFOAM.com	Emergency Phone:	CHEMTREC: 800-424-9300

Section 2: Hazard Identification

Classification of the substance or mixture:

GHS Classification:	
Skin irritation, Category 3	• Eye irritation, Category 2

Label Elements

Η	azardous components which must be listed on label:	
٠	Tertiary Amine Catalysts	•

GHS Labeling:



Ha	zard Statements:		
•	May cause skin irritation	•	May cause eye irritation
•	May cause respiratory irritation		

Pre	ecautionary Statements:		
•	Do not breathe fume/gas/mist/vapors/spray	•	Wear protective gloves/eye protection/face protection
•	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	•	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
•	IF ON SKIN: Wash with plenty of soap and water		

Other Hazards:





145 Newborn Road • Rutledge, GA 30663 706.557.1400 • <u>www.PROFOAM.com</u>

Section 3: Composition

Hazardous Components

Type of product: Mixture

CAS#	Weight %	Name
Proprietary	< 9	Tertiary amine catalysts

Section 4: First Aid Measures

Inhalation:	Move to fresh air if symptoms develop. If breathing is difficult, give oxygen and call physician.	
Eye Contact:	Flush with water for at least 15 minutes. See a physician if irritation develops.	
Ingestion:	Do not induce vomiting unless told to do so by a medical professional.	
Most Important symptoms and effects, acute and delayed:	May cause skin or eye irritation upon contact. Avoid breathing vapors. The dense vapors can displace and reduce breathing air in confined or unventilated spaces causing asphyxiation. Overexposure may cause tremors, confusion, irritation, and may result in cardiac sensitization.	
Indication of immediate medical attention and special treatment, if applicable:	N/A	
Skin Contact:	Wash with soap and water at first opportunity.	

Section 5: Fire-Fighting Measures

Suitable extinguishing media:	Water, dry chemicals, CO ₂
Unsuitable extinguishing media:	None
Special hazards arising from the chemical:	None
Precautions for fire-fighters:	A self-contained breathing apparatus should be worn to protect against toxic and irritating vapors.

Section 6: Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures:	Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.
Environmental precautions:	Do not discharge into drains/surface waters/groundwater
Methods and material for containment and cleanup:	Absorb with sawdust, etc., and shovel into container. Waste material should be disposed of under conditions which meet federal, state, and local environmental regulations.





145 Newborn Road • Rutledge, GA 30663 706.557.1400 • <u>www.PROFOAM.com</u>

Section 7: Handling and Storage

Precautions for safe handling:	Store between 65°F and 85°F out of sunlight. Relieve pressure slowly when opening container.
Conditions for safe storage, including any incompatibilities:	Keep tightly sealed.

Section 8: Exposure Controls and PPE

Exposure Limits

Туре	Value
TWA	None established

¹Not listed as a carcinogen (NTA, IARC, OSHA)

Exposure Controls

Respiratory Protection:	The specific respirator selected must be based on contamination levels of this material found in the workplace and the working limits of the respirator. A supplied air, full-face mask, positive pressure or continuous flow respirator or a supplied air hood is required when airborne concentrations are unknown or exceed threshold limit values. A positive pressure, self-contained breathing apparatus can be used in emergencies or other unusual situations. Full-face air purifying respirators equipped with organic vapor cartridges can be used in certain situations, <i>see OSHA standard 29CFR 1910.134</i> . All equipment must be NIOSH approved and maintained.
Hand, eye, skin, body	Wear goggles or chemical safety glasses and chemically resistant rubber or plastic gloves.
protection:	Avoid eye and skin contact. Eye wash system and showers should be available.

Section 9: Physical and Chemical Properties

Basic chemical and physical properties

Appearance:	Liquid	Flammability:	N/A
Color:	Amber	Upper/lower flammability or	N/A
Odam	Faint ammonia odor	explosive limits:	N/A
Odor:		Vapor pressure:	
Odor threshold:	N/A	Vapor density:	N/A
pH:	N/A	Relative density:	1.13 g/mL
Melting pt/freezing pt:	<32°F	Solubility(ies):	highly soluble in water
Boiling pt/boiling range:	>200°F	Partition coefficient (n-	N/A
		octanol/water):	
Flash point:	>200°F	Auto-ignition temperature:	>500°F
Evaporation rate:	Slower than ether	Decomposition temperature:	>500°F



145 Newborn Road • Rutledge, GA 30663 706.557.1400 • <u>www.PROFOAM.com</u>

Section 10: Stability and Reactivity

Chemical stability:	Stable	
Possibility of hazardous reactions:	N/A	
Conditions to avoid:	N/A	
Incompatible materials:	Isocyanates and other chemicals that react with hydroxyl groups.	
Hazardous decomposition products:	When burned, CO, CO ₂ , NO _x aliphatic fragments, halogens, halogen acids, and possibly	
	carbonyl halides.	

Section 11: Toxicological Information

Acute toxicity:	May cause skin irritation
Chronic toxicity:	Not available
Likely routes of exposure:	Skin
Symptoms related to physical, chemical and toxicological	May cause skin irritation
characteristics:	
Delayed and immediate effects and chronic effects from	May cause skin irritation; avoid contact with eyes
short and long-term exposure:	
Numerical toxicity measures:	Not available

Section 12: Ecological Information

Ecotoxicity:	Not a marine pollutant
Persistence and degradability:	No known significant effects
Bioaccumulative potential:	Does not bioaccumulate
Mobility in soil:	

Section 13: Disposal

Waste disposal:	R component drums can be sent to drum reconditioners or disposed of as ordinary industrial waste in
	compliance with pertinent regulations

Section 14: Transport

UN number:	Not regulated
UN Proper shipping name:	Not regulated
Transport Hazard class(es):	Not regulated
Packing group, if	Not regulated
applicable:	
Marine pollutant (YorN):	Ν
Special precautions:	None



145 Newborn Road • Rutledge, GA 30663 706.557.1400 • <u>www.PROFOAM.com</u>

Section 15: Regulatory

Relevant safety, health, and environmental regulations

Inventory Status:	All components TSCA listed
US Regulations:	No ingredients listed
US Superfund Amendments and Reauthorization Act	No ingredients listed
(SARA) Title III Section 313 information:	

Section 16: Other

SDS Preparation Date:	07/03/2018
Revision Date:	

IMPORTANT NOTICES

This notification is a part of the Safety Data Sheet document and must not be detached. Any copying and redistribution of the Safety Data Sheet shall include copying of this notice and attaching the copy to the redistributed Safety Data Sheet copies.

This information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of Profoam. The data on this sheet relates only to the specific material designated herein. Profoam assumes no legal responsibility for use or reliance upon these data.