





HYDRA[®] X

BUILT FOR MAXIMUM DURABILITY AND POWER THE TITAN HYDRA X SERIES DELIVERS WHEN THE JOB CALLS FOR THE TOUGHEST COATINGS.

With a Direct Immersion System that means no transfer pumps, flexible siphon tubes, or air compressors needed, the Hydra X Series from Titan maximizes your efficiency on the jobsite. Featuring limit-sensing hydraulics for better control and interchangeable fluid sections, an AutoLift[™] system raises and lowers the fluid section with the push of a button; and more the Hydra X delivers when the job calls for the toughest coatings.

HYDRASTROKE[™] TECHNOLOGY

- Unmatched durability and performance powered by electronically controlled hydraulics.
- Unlike clutch units that small tips can damage, the Hydra X has the versatility to spray heavy and light bodied coatings with ease
- Hydraulic motor is optimized with one moving part, reducing heat and extending life



SEVERE SERVICE[™] FLUID SECTION

- 5" long, slow stroking piston maximizes power and efficiency to extend the pump life
- Uses a Tri-chrome process to create the industry's most durable fluid section with packings designed specifically for aggressive coatings
- Proven Titan self-adjusting packing technology with over 45 years in the field extends time between repacks
- New patent pending quick removal fluid section allows one person to service on the jobsite with ease

SMART DESIGN

- Effortless drum changes with the electric AutoLift[™] system that raises and lowers the fluid section with the touch of a button
- One sprayer with modular fluid sections allowing for two different performances out of one sprayer
- Large 12" pneumatic tires make it easy to move around job site

EXTREMELY EFFICIENT COOLING SYSTEM

- Two cooling fans to maximize air flow over hydraulic system
- Large 6 gallon hydraulic fluid reservoir

Powered by HONDA®

A WORKHORSE FOR ANY JOBSITE

- Roofing
- Bridges
- Railroad
- Cargo Containers
- Commercial Construction

WHY HYDRA?

- Industry Leading Performance
- Eliminates the Need for Transfer Pump
- Meets Needs of Multiple Market Segments

- Residential Construction
- Secondary Containment
- Below Grade
 Waterproofing
- Versatile Application
- Field Serviceable Quick-Change Fluid Section
- Efficient Hydraulics
- Minimal Down Time

CUSTOMIZE YOUR HYDRA X SPRAYER

| | | 0.0.0.0.0.0.0 |
|-------------------------------|---------------|---------------|
| SPRAY GUNS | | |
| DESCRIPTION | MAX. PRESSURE | PART NO. |
| RX-Apex Non-Filtered Gun | 5000 psi | 538070 |
| RX-Apex Filtered Gun | 5000 psi | 538075 |
| S-7 Gun with 1/4" Swivel | 7700 psi | 550-260 |
| S-7 Gun with 3/8" Swivel | 7700 psi | 550-270 |
| M-8 Mastic Gun w/ 1/4" Swivel | 7700 psi | 289014 |
| M-8 Mastic Gun w/ 3/8" Swivel | 7700 psi | 2425442 |
| Multi Gun Manifold | 7700 psi | 2414176 |

| SPRAY TIPS | | |
|------------------------------------|---------------|----------|
| DESCRIPTION | MAX. PRESSURE | PART NO. |
| TR ¹ Tips | 5000 psi | 695-XXX |
| TR ¹ High Pressure Tips | 7700 psi | 696-XXX |
| SC-6+ Tips | 5000 psi | 662-XXX |
| SC-6+ Widespray Tips | 5000 psi | 661-XXX |

| ACCESSORIES | | |
|-------------------------------------|---------------|----------|
| DESCRIPTION | MAX. PRESSURE | PART NO. |
| No Build Tip Guard 7/8" | 5000 psi | 289228 |
| High Pressure Tip Guard 7/8" | 7700 psi | 661-027 |
| Black Seal, Latex | 5000 psi | 651-042 |
| White Seal, Solvent Resistant | 7700 psi | 651-020 |
| 1/8" Gasket Kit 12-Pack | | 711-612 |
| 1/16" Gasket Kit 12-Pack | | 711-606 |
| 6" (15 cm) Gun Extension | 7700 psi | 611-280 |
| 12" (30 cm) Gun Extension | 7700 psi | 611-281 |
| 18" (45 cm) Gun Extension | 7700 psi | 611-282 |
| 24" (60 cm) Gun Extension | 7700 psi | 611-283 |
| Closed Drum Sealed Siphon | | 2426217 |
| Flexible Tote Siphon | | 2410501 |
| Hydra X 4540 to 7230 Conversion Kit | | 2424618 |
| Hydra X 7230 to 4540 Conversion Kit | | 2432905A |

Note: Converting the 4540 to the 7230 will change the fluid section pressure to 6900 psi. Converting the 7230 to the 4540 will change the fluid section pressure to 4650 psi.

| 7500 PSI MOISTURE RESISTANT HOSE | | |
|----------------------------------|-------------|----------|
| DIAMETER | MAX. LENGTH | PART NO. |
| 3/8" | 50 feet | 2389440 |
| 1/2" | 50 feet | 2389442 |
| 3/4" | 50 feet | 2426011 |
| | | |

| 4500 PSI HOSE | | |
|---------------|-------------|----------|
| DIAMETER | MAX. LENGTH | PART NO. |
| 1/4" | 3 feet | 2389428 |
| 1/4" | 6 feet | 2389430 |
| 1/4" | 50 feet | 2389429 |
| 1/4" | 100 feet | 2389427 |
| 3/8" | 6 feet | 2389436 |
| 3/8" | 50 feet | 2389434 |
| 3/8" | 100 feet | 2389432 |
| 1/2" | 50 feet | 2389425 |
| 1/2" | 100 feet | 2389424 |

| 7500 PSI HOSE | | |
|---------------|---|--|
| MAX. LENGTH | PART NO. | |
| 3 feet | 2389450 | |
| 6 feet | 2389452 | |
| 50 feet | 2389451 | |
| 100 feet | 2389449 | |
| 6 feet | 2389456 | |
| 50 feet | 2389455 | |
| 100 feet | 2389453 | |
| 50 feet | 2389448 | |
| 100 feet | 2389447 | |
| 50 feet | 2426010 | |
| | MAX. LENGTH 3 feet 6 feet 50 feet 100 feet 6 feet 50 feet 100 feet 50 feet 100 feet 50 feet 100 feet 100 feet | |

Note: Hydra X units are sold bare

DON'T TAKE



"The Hydra X has performed flawlessly and is just more productive than the other pumps. Now I'll need less pumps on the jobsite. That means less pumps to run and maintain. That's huge."

> Mike Ottelien, Owner MO Decorating & Remediation Racine, WI



QUALIFYING QUESTIONS

What tip sizes do your coatings require? How many guns?

| | HYDRA X 4540 | HYDRA X 7230 |
|----------------|--------------|--------------|
| NUMBER OF GUNS | MAX TIP SIZE | MAX TIP SIZE |
| 1-Gun | 0.067" | 0.057" |
| 2-Guns | 0.043" | 0.035" |
| 3-Guns | 0.035" | 0.031" |
| 4-Guns | 0.031" | 0.027" |
| 5-Guns | 0.025" | 0.021" |
| 6-Guns | 0.021" | |

How many gallons do you spray a week?

• These are durable pumps made to last through all day usage 7 days a week

Power needed

• Both units are equipped with a Honda GX390 gas engine

What are your hose length requirements?

• Depending on material being used Titan recommends 300' max for the 4540 and 400' max for the 7230

| | HYDRA X 4540 | HYDRA X 7230 |
|--------------------------------------|---------------------|--------------------|
| SPECIFICATIONS | | |
| Max. Delivery | 4.0 gpm (15.1 lpm) | 3.0gpm (11.4 lpm) |
| Max. Operating Pressure | 4500 psi (31.0 MPa) | 7200 psi (49.6MPa) |
| Max. Tip Size (1-Gun) | 0.067" | 0.057" |
| Volumetric Flow per Double Stroke | 247 CC | 162 CC |
| Cycles Per Gallon | 15 | 23 |
| Weight | 385 lbs | 385 lbs |
| UPC | 024964295869 | 024964295876 |
| Part No. | 2412275 | 2412277 |

Hydra X 7230

Powerful high pressure sprayer for hard to atomize materials like silicone and epoxies.

Use if you're primarily spraying:

- Silicone
- Epoxy
- Elastomeric



| COMMON COATINGS | | |
|--------------------------|--------------|--------------|
| COATINGS | HYDRA X 4540 | HYDRA X 7230 |
| Latex | Х | Х |
| Primers | Х | Х |
| Block Filler | Х | Х |
| Enamel | Х | Х |
| Elastomerics | Х | Х |
| Acrylics | Х | Х |
| Ероху | | Х |
| Polyester | Х | Х |
| Polyurethane | Х | Х |
| Fibered Asphalt Emulsion | Х | Х |
| Coal Tar | Х | Х |
| Mastics | Х | Х |
| Water Proofing | Х | Х |
| Contact Cement | Х | Х |
| Cut-Back Asphalt | Х | |
| Joint Compound | Х | |
| Aluminum Emulsion | Х | Х |
| Acrylic Elastomeric | Х | Х |
| Emulsion Primer | Х | Х |
| Silicone | | Х |
| Intumescents | | Х |

We are actively testing coatings for the Hydra X Series, if you have questions about coating compatibility contact our Technical Service Department at 1-800-526-5362



Hydra X 4540

Excellent for high solids elastomeric and high production. Use if you're primarily spraying:

- Acrylic Elastomeric Roof Coatings
- Asphalt Emulsion
- Zinc Coatings
- Commercial Architectural Coatings

HYDRA[®] X FEATURE MAP

ah"

AUTOLIFT™ SYSTEM Raises the fluid section to easily change out drums or pails

HYDRASTROKE[™] | TECHNOLOGY

- Cool running, durable hydraulics
- Stroke detection senses top and bottom for precision control limits
- Regenerative circuit keeps pressures balanced from upstroke to downstroke

FIELD-SERVICEABLE | FLUID SECTION

With only a hammer, one person can easily swap out fluid sections on the jobsite minimizing downtime

LARGE HOSE WRAP Holds up to 200' of 1/2" hose

HONDA GX390 ENGINE

- Fuel efficient with all the power and performance of a Honda
- Low oil alert system prevents engine seizure
- Electric start

DUAL FAN COOLING

12" PNEUMATIC TIRES AND BALANCED CART

For easy maneuverability

AUTOMOTIVE STYLE RADIATOR Optimized to keep system cool

TITAN

HYDRA

DID YOU KNOW...

By purchasing a fluid section conversion kit you can switch performance from one pressure and gpm to the other by simply changing the fluid section. Yes. Two machines in one!

HYDRA X 4540 TO 7230 CONVERSION KIT 2424618

HYDRA X 7230 TO 4540 CONVERSION KIT 2432905A



HYDRA X 4540

CONVERSION KIT

HYDRA X 7230

FREQUENTLY ASKED QUESTIONS

CAN YOU USE THIS SPRAYER WITH A CLOSED 55 GALLON DRUM?

Yes, if you purchase the siphon accessory (2426217) the unit will work with an enclosed drum and create a sealed system.

WILL THESE SPRAYERS HANDLE SOLVENT BASED MATERIALS?

Yes, both sprayers are compatible with all common solvents

WHAT BATTERY COMES WITH THE HYDRA X?

The Hydra X comes with a fully sealed battery ready to go, no acid needed.

IF I BUY A 7230 CAN I CONVERT IT INTO A 4540?

Yes, with the interchangeable fluid section you can convert from 7230 to 4540 and vice versa.

WILL THESE SPRAYERS HANDLE AGGREGATED MATERIALS?

No, the piston pump will pack out with aggregated materials

CAN I LIFT THE SPRAYER ON TOP OF A ROOF USING A CRANE?

Yes, use the approved strap and follow lift instructions in the manual

CAN I SPRAY OUT OF A 5 GALLON BUCKET IF I'M NOT USING A DRUM?

Yes, you can spray out of a 5 gallon bucket with the Hydra X Series



BEST AND LONGEST WARRANTY IN THE INDUSTRY TITANWEARGUARD.COM Titan delivers unmatched quality and we are not afraid to stand behind our work with the best and longest warranty in the industry including a four-year manufacturer's defect. If you ever need help, contact your nearest dealer or service center and we will take care of the job so you can stay focused on spraying.



titantool.com

Titan Tool 1770 Fernbrook Lane Minneapolis, MN 55447 1-800-526-5362

All information contained in this brochure is based on the latest information available at the time of printing. Titan reserves the right to make changes at any time, without notice. Due to continuous innovation, specifications may progressively change. Contact one of our dependable sales reps or call our dedicated customer service team for more information.