Safety Data Sheet E236 Urethane Mold ReleaseTM



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated	Product Name:	Urethane Mold Release [™]
1070 Robert Fulton Hwy.	Product Code:	E236
Quarryville, PA 17566	Product Use:	Mold Release
1-800-227-5538	24-hour emergency phone:	1-800-424-9300 [CHEMTREC]
2. HAZARD IDENTIFICATION	I	
POTENTIAL HEALTH EFFECTS		
Classification of the chemical in accordance GHS Hazard Symbols	e with paragraph (d) of §1910.1200;	
GHS Classification	Gases under pressure - Liquified Gas Flammable Aerosol Category 2	
Signal Word	Warning	
Hazard Statements	Flammable aerosol. Contains gas under pressure; may explode if heated.	
Precautionary Statements		
Prevention	Keep away from heat/sparks/open flames/hot surfaces. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after	
Storage	Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do no expose to temperatures ex	ceeding 50°C/ 122°F.

3. COMPOSITION/INFORMATIO	ON ON INGREDIENTS				
COMPONENT Halogenated hydrocarbon/ether blend	<u>CAS #</u> Mixture		Percent 80-100		
HMIS® III* HAZARDOUS WARNINGS: Health: 1 Flar	nmability: 2	Physical:	2	Personal Protective Equipment:	See Section 8
* See www.paint.org/hmis or call the ACA at 1 ((202) 462-6272 for more informatio	on on this current rating syste	m.		
4. FIRST AID MEASURES					
Eves: Immediately fluch eves as	antly with planty of water for at least	t 15 minutos while helding a	valida apart If av	motoms parsist or there	

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there
	is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. For liquid contact, treat for
	frostbite if necessary. Seek medical attention if symptoms persist. Wash clothing before reuse.
Ingestion:	Contact a physician, medical facility, or poison control center immediately.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical
	attention.

NOTES TO PHYSICIAN:

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support.

Stoner Incorporated

E236

PAGE 1

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:

Fire Fighting Instructions:

This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.Containers may rupture or explode under fire conditions. This material burns with difficulty, but will support combustion. Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. If runoff occurs, notify authorities as required.

7. HANDLING AND STORAGE

Handling: Use with adequate ventilation. Do not use near ignition sources. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. May cause frostbite. Inhalation of respirable aerosols of the lubricant in this product may cause serious toxic effects in the lungs, based on animal studies. Use proper PPE. Usual precaution for combustible liquids. Wash hands thoroughly after handling.
Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 122 degrees F. Empty

Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 122 degrees F. Empty container may contain residues which are hazardous. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Ground all equipment and cylinders before use. This material (or a component) evolves flammable methyl alcohol when exposed to water or humid air.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Mixture

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects).			
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.			
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.			
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol. The use of an approved dust, fume and mist respirator designed for exposure limits greater than 0.05 mg/m3 is recommended.			
COMPONENT	CAS # ACGIH TLV OSHA PEL OTHER			

Not established

Not established

1000ppm TWA (Mfr.)

Halogenated hydrocarbon/ether blend

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Colorless	Upper Flammability Limit (%):	Not applicable
Odor:	Slight Ether	Vapor Pressure (PSIG @ 70°F):	78.0
Odor Threshold:	Mild	Vapor Density $[air = 1]$:	>1
pH:	Not applicable	Relative Density (H2O=1):	0.8
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Not determined
Boiling Point (°F):	No data available	Partial Coefficient: n- octanol/water:	No data available
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	Not applicable
Evaporation Rate:	No data available	Decomposition Temperature (°F):	No data available
Flammability (solid, gas): Percent VOCs (%):	No data available 40 - 60	Viscosity, dynamic (cSt):	No data available

10. STABILITY AND REACTION

Chemical Stability: Conditions to Avoid:

Decomposition Products:

Stable

Avoid contact with: Alkali. Alkaline earth metals. Powdered metals. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Oxidizers. Acetic acids Organic acid anhydrides. Strong oxidizing agents. This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride. If heated with peroxides present, violent decomposition can occur. When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm. Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Inhalation Toxicity:

Inhalation of respirable aerosols of the lubricant in this product may cause serious toxic effects in the lungs, based on animal studies. Use proper PPE. No data available.

Reproductive & Developmental Toxicity: IARC Carcinogen Designation:

on: No data available

Stoner Incorporated

E236

PAGE 2

Ingredien No data av		CAS #	Toxicological Data	
12. ECOLOGICAL INFORMATION				
Ecological Mobility:	Toxicity:	No data available No data available		
Ingredie Ether pro		CAS # 115-10-6	Toxicological Data 48HR NOEC GUPPIES > 4000 mg/L 48HR NOEC Daphnia > 4000 mg/L No data available	
13. DIS	POSAL CONSI	DERATIONS		
Disposal :	Dispose accord	ing to Federal, State and local regulations.		
14. TRA	ANSPORTATIO	ON INFORMATION		
Agency DOT IATA IMDG † "Limited	UN Number UN1950 ID8000 UN1950 I Quantities" may be a	Proper Shipping name Aerosols, Flammable† Consumer Commodity† Aerosols, Flammable† applicable for this transportation mode.	Hazard Class 2.1 9 2.1	Packing Group Not applicable Not applicable Not applicable
15. REGULATORY INFORMATION				
Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below: COMPONENT CAS # % BY WEIGHT Regulatory Body No components listed in this section. SARA Section 313 Toxic Substances Control Act Sara Section 313				
All components of this product are listed on the TSCA inventory.				
California Prop 65 This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.				

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 12/14/17

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.